



QTY	MODEL NUMBER	NOMINAL SIZE		OVERALL LENGTH		LIVE LENGTH		STATIC BEND RADIUS		CONSTANT FLEXING BEND RADIUS		MAXIMUM OPERATING PRESSURE @ 70°F (21°C)	
		INCHES	mm	INCHES	mm	INCHES	mm	INCHES	mm	INCHES	mm	PSIG	KPaG
	UFPH-12-12	3/4	19	12	305	7.5	191	4.3	109	8	203	150	1,035
	UFPH-12-18	3/4	19	18	457	13.5	343	4.3	109	8	203	150	1,035
	UFPH-12-24	3/4	19	24	610	19.5	495	4.3	109	8	203	150	1,035
	UFPH-12-36	3/4	19	36	914	32.5	826	4.3	109	8	203	150	1,035
	UFPH-16-12	1	25	12	305	7.25	184	5.5	140	8.4	213	150	1,035
	UFPH-16-18	1	25	18	457	13.25	337	5.5	140	8.4	213	150	1,035
	UFPH-16-24	1	25	24	610	19.25	489	5.5	140	8.4	213	150	1,035
	UFPH-16-36	1	25	36	914	31.25	794	5.5	140	8.4	213	150	1,035

NOTES:

- 1) Assembly to be designed, fabricated and tested in accordance with ASME code section VIII and IX, ANSI B31.3 and CSA B51 code. Welding to be as per ASME BPV code, and performed by qualified welders in accordance with the codes.
 - 2) Assembly to be S.S. tagged on one collar.
 - 3) Assembly shall be tagged on the second collar with the UL/ULC yellow tag.
- ULC symbol – Manufacturer Listing Number – Max. Working Pressure: 150 PSIG

4	2	HEX MALE NPT	SS 304
3	2	BRAID RETAINING COLLAR	SS 304
2	1	STANDARD BRAID	SS 304
1	1	HELICAL CORRUGATED METAL HOSE	SS 321
ITEM	QTY	DESCRIPTION	MATERIAL

S.S TAG:
FLEX-PRESSION LTD.
PART NUMBER: UFPH-XX-XX
MANUF. NO.:
DATE OF MANUF.:

BILL OF MATERIAL

THIS DOCUMENT IS THE PROPERTY OF FLEX-PRESSION LTD. & FLEX-PRESSION (ONTARIO) LTD. AND THE DATA HERE IN IS NOT TO BE DISCLOSED IN ALNY FORM TO ANYONE WITHWOUT THE WRITTEN PERMISSION OF FLEX-PRESSION LTD. OR FLEX-PRESSION (ONTARIO) LTD.

CUSTOMER:

ALBANY PUMP COMPANY LTD.
 420 HARRY WALKER PARKWAY N.
 NEWMARKET, ONTARIO L3Y 8P5
 TEL: 905-853-9005 – FAX: 905-853-3565



FLEX-PRESSION LTD.

Sold by: **albany**
pump company ltd.
 888-334-3348
 sales@albanyump.com

DRAWING TITLE:

MODEL UFPH
 BRAIDED STAINLESS STEEL FLEXIBLE CONNECTOR
 WITH MALE NPT HEX STAINLESS STEEL WITH UL/ULC
 CERTIFICATION

DRAWING No.

UFPH-1216

Rev.

0